

Covert/Disguise HD High Definition Surveillance Cameras

Available Configurations

LXCHDF Simulated Fire Alert/Sensor

2.43 Megapixel, Sony Exmor CMOS Image Sensor, 1080p NTSC/PAL selectable; 3.6mm, 6mm, 8mm and 12mm lens option. One or two camera configuration: adjustable angle of view.

LXCHDDJ Simulated RJ-45 Data Jack

2.43 Megapixel, Sony Exmor CMOS Image Sensor, 1080p NTSC/PAL selectable; 3.5-16mm varifocal lens option.

LXCHDMD Three-Axis Varifocal Mini-Dome

2.1 Megapixel, Sony Exmor CMOS Image Sensor, 1080p; 12mm lens option.

LXCHDPTZ Pan/Tilt/Zoom Speed-Dome with Three-Axis Controller

Superlative 1080p HD resolution for amazing image quality; Sony Exmor progressive CMOS image sensor, 12X 4.8mm-57.6mm optical zoom lens option.

LXCHDSD Simulated Smoke Sensor

2.1 Megapixel, Sony Exmor CMOS Image Sensor, 1080p NTSC/PAL selectable; 4.3 mm fixed pinhole lens option.

LXCHDPIR Simulated Motion Detector

2.1 Megapixel, Sony Exmor CMOS Image Sensor, 1080p NTSC/PAL selectable; 3.7 mm fixed pinhole lens option.

LXACV BNC/DC Video Installation Cables

Copper shielded RG-59 18/2 high-grade video/power cable for high-definition video camera installation.